



“The First in Synthetics”

*For Outstanding Performance
In Two-Cycle Gasoline Engines*

PRODUCT DESCRIPTION

AMSOIL Synthetic 2-Cycle Oils are superior quality lubricants which provide maximum protection and outstanding performance in two-cycle gasoline engines.

Maximum Wear Protection

AMSOIL Synthetic 2-Cycle Oils are high film strength oils that virtually eliminate metal to metal contact so piston scuffing is prevented and wear is reduced. The high lubricity of AMSOIL 2-Cycle Oils reduces friction so operating temperatures are controlled and maximum engine performance is achieved.

Reduced Engine Deposits

AMSOIL Synthetic 2-Cycle Oils contain top performing additives which have been tested and proven to minimize high temperature deposits. These oils resist oil breakdown from heat so they do not form gum, varnish, sludge or sticky deposits. Spark plug fouling and excessive carbon build-up in the combustion chamber, exhaust port and ring area are greatly reduced. In addition, the clean burn characteristics and lean mix ratios reduce smoke and exhaust emissions.

Prevents Rust and Corrosion

AMSOIL Synthetic 2-Cycle Oils contain special rust and corrosion inhibitors, providing excellent off-season storage protection.

Outstanding Low Temperature Performance

Both AMSOIL Synthetic Injector Oil and 100:1 Pre-mix Oil mix readily with fuel even in low temperatures. However, AMSOIL Injector Oil with its -45°F pour point and SAE #4 miscibility and fluidity rating, is better suited for severe cold. It is recommended for use in injector systems as well as 50:1 pre-mix. Also, AMSOIL injector oil will help ease starting because it does not solidify or get gummy in the motor which allows it to turn over more freely,

SYNTHETIC 2-CYCLE OILS INJECTOR OIL AND 100:1 PRE-MIX OIL

Meet or Exceed the Following:

- API TC
- NMMA TC-WII, TC-W3
- JASO FC
- ISO EGD

APPLICATION RECOMMENDATIONS

ATC 100:1 PRE-MIX

AMSOIL Synthetic 100:1 Pre-Mix 2-Cycle Oil (ATC) is recommended for all water-cooled and air-cooled pre-mix applications. A mix ratio of 100:1 is recommended for normal duty service in applications such as motorcycles, outboard motors, weed eaters, lawn mowers and chain saws. Richer mix ratios of 50:1 to 80:1 are recommended for severe duty service such as racing applications, ultra-light “kit” type airplanes and for hot operating industrial use motors that run for extended periods of time.

AMSOIL Synthetic 100:1 Pre-Mix 2-Cycle Oil is recommended for all pre-mix applications specifying TC-W3, API TC, JASO FC and ISO EGD. It is recommended for use with gasoline fuels only, and is not recommended for use in oil injection systems.

APPLICATION RECOMMENDATIONS

AIO INJECTOR OIL

AMSOIL Synthetic 2-Cycle Injector Oil (AIO) is recommended for use in all summer and winter two-cycle injector applications and for pre-mix applications at 50:1 mix ratios. Use AMSOIL 2-Cycle Injector Oil wherever TC-W3 or API TC oils are specified in water-cooled or air-cooled motors. AMSOIL Synthetic 2-Cycle Inject Oil is recommended for all two-cycle injector applications, including outboard motors, snowmobiles, motorcycles, ATVs and personal watercraft. AMSOIL Synthetic 2-Cycle Injector Oil is compatible with and recommended for two-cycle applications using catalytic converters.

AMSOIL Synthetic 2-Cycle Injector Oil is compatible with other synthetic and petroleum TC-W3 type oils and may be mixed with them. It is recommended for use with gasoline fuels only.

TYPICAL TECHNICAL PROPERTIES

AMSOIL Injector and 100:1 Synthetic 2-Cycle Oils

	100:1 Oil (ATC)	Injector Oil (AIO)
Kinematic Viscosity @ 100°C, cSt (ASTM D-445)	10.88	7.5
Kinematic Viscosity @ 40 C, cSt (ASTM D-445)	82.87	43.7
Pour Point, °C [°F] (ASTM D-97).....	-28 (-18).....	-43 (-45)
Flash Point, °C [°F] (ASTM D-92)	264 (507).....	92 (198)
Color	Blue	Blue
SAE Miscibility/Fluidity Grade	2.....	4
Recommended for applications specifying:		
API Service Classification.....	TC	TC
NMMA Rating	PC-W3 (Pre-Mix).....	TC-W3
JASO	FC	
ISO	EGD	

AMSOIL PRODUCT WARRANTY

AMSOIL INC. warrants that the use of its lubricants will not cause mechanical damage to any mechanically sound equipment when AMSOIL INC. products are used in full compliance with the company's recommendations.

AMSOIL products and Dealership Information are

Available from:

Chuck Burnell—AMSOIL Dealer
Pecuniary, Inc.
9424 Springdale Dr., Raleigh, NC 27613
Toll Free: 1-8778-AMSOIL
877-826-7645
Fax: 919-870-9633
Email: cburnell@pecuniary.com
[Http://www.pecuniary.com](http://www.pecuniary.com)

